

Very fast:
140mm/sec

Small Size



Nice Design

Easy Loading

Reliable

Thermal Desktop Printers

Neo's

Neo's

High performance thermal desktop printer for paper width 60mm and high printing speed up to 140mm/sec. Small and reliable, neo's is suitable as kitchen printer, for coupons, receipts or invoices printing and connected to POS cash systems; the printer is the right solution for measurement and control instruments and medical equipments.

Neo's PS with internal power supply. Easier paper loading thanks to the access from front and to autoloading system.

Optional cutter (total and partial cut). Interfaces: RS232 and RS485.

All models are available with cash drawer control and drivers (Windows and Linux) and software tools to create and update logos and fonts.

Most common barcodes printing: UPC-A, UPC-E, EAN 13, EAN 8, CODE 39, ITF, CODABAR, CODE 128, CODE 32 PHARMACEUTICAL, CODE 93.

Double colour printing (red/black - blue/black).

Neo's PS USB model with USB interface is also available.

Neo's PS RF neo's printer with internal power supply for receipts and invoices. This model allows the ticket alignment thanks to additional commands on printer firmware.

Neo's 24 with 24Vdc external power supply (optional). Available interfaces for this model are serial RS232 or parallel Centronics.





Neo's PS

Neo's PS USB

Neo's 24

Printing Method	Thermal fixed head (8 dot/mm)		
Resolution	203 dpi		
Printing Speed (mm/s)	Low >110 Normal >140		
Character Set	ASCII standard, International		
Type Styles	Normal, double and quadruple height and width, reverse, underscored, italic, bold		
Printing Direction	Straight, 180°		Straight, 90°, 180°, 270°
Paper Width	60 ± 0.5 mm		
Roll Dimension	max 65 mm		
Emulation	ESC/POST™		
Interface	RS232, RS485	USB	RS232, Centronics
Baud Rate	From 1.200 to 57.600 bps	none	From 1.200 to 57.600 bps
Data Buffer	8 Kb		
Flash Memory	256 Kb		
Graphic Memory	3 logos of 32 Kb		
Drivers	Windows™ 95, 98, me, NT4, 2K, XP; Linux		
Software Tools	Logo Editor, Font Editor		
Power Consumption	1 A		
Power	90-240 Vac, 50/60 Hz		24 Vdc ± 10% (optional external power supply)
DKD Function	1 driver		
Reliability MTBF	50 Km		
Safety	EN60950 +A1 +A2 +A3 +A4		
Dimension (LxWxH)	170x120x100 mm (h=110mm with cutter)		
Options	Partial Cut		



Very fast
140mm/sec

CUSTOM ENGINEERING SPA

World Headquarters
Via Berettine, 2 - 43010 Fontevivo, Parma ITALY
Tel. +39 0521 680111 - Fax +39 0521 610701
info@custom.it - www.custom.it

Branch Offices

CUSTOM ENGINEERING MILAN
Via Pavia, 10 - 20053 Muggiò, Milano ITALY
Tel. +39 039 2144280 - Fax +39 039 2144249
custom.milano@custom.it


CUSTOM ENGINEERING MODENA
V.le Virgilio, 56D - 41010 Modena ITALY
Tel. +39 059 8869511 - Fax +39 059 8869512
custom.modena@custom.it

CUSTOM ENGINEERING UK LTD
6 Carmelite Road
LUTON LU40NH UK
Tel. +44(0)1582 605579 - Fax +44(0)1582 605579
uk.sales@custom.it

CUSTOM ENGINEERING USA
625 West University Drive, Unit C
Arlington Heights, IL 60004 USA
Tel. +1 847 818 1260 - Fax +1 847 818 1287
us.sales@custom.it

also available

Smice POS



Smice.com



Label
Printers



DTK



s'print



DP



KIUBE

